ECB 450 BIODEGRADABLE EROSION CONTROL PRODUCTS

ECB 450 - Temporary erosion control products 100% photodegradable and biodegradable : coir mat.



What is ECB 450?

Coir (coconut fibre) usage has become widespread in various industries due to its versatility. Coir has established a remarkable reputation in horticulture, agriculture and erosion control as being superior to other available natural materials. Unlike agriculture and horticulture which have used coir for hundreds of years, coir is relatively new to erosion control and it may take some time before it is fully recognised.

Appreciation of coir erosion control has resulted from the fact that it is an abundant and renewable natural resource with an extremely low decomposition rate and high strength compared to other natural fibres. In ECB (erosion control blanket) applications, blankets made of coir are well known for superior performance compared to other organic blankets. The fast growth of environmentally concerned designers with their cutting edge bioengineering designs has increased coir use in erosion control.

Coir is typically processed from the ripe coconut husks which are dark brown in colour and have been retted in fresh water for at least six months. The retting process acts as a curing process for fibres. Curing in freshwater increases resistance to UV (ultraviolet) degradation and also increases the flexibility of processed fibre without causing deterioration. During traditional processing, coconut fibre from cured husks is separated by skilled labour into grades depending on the length of fibre. The longer and stronger fibres are called bristle coir and the shorter and thinner fibres are called mattress coir.

Advantages of ECB 450 as an erosion control material:

- Moisture absorption: factor 9 times its dry weight (900%)
- Retains humidity in the soil and atmosphere
- Slows discharge of water
- Excellent at reducing soil erodability
- Resists temperature and wind extremes
- Promotes and protects healthy growth of vegetation
- Biodegrades within time scale

- Poses no future problems for farmers, horticulturists or maintenance teams
- Protects against rain splash erosion and wind erosion
- Moderates extremes of temperature
- Protects against direct sun and desiccation
- Low Cost

Areas of Application:

- Over steepened slopes, road, rail, embankments, industrial, mining restoration and earth dams
- Drainage channels, culvert outlets, washout drains and emergency water courses
- Highly erodible soils (embankments and sandy/silty soil areas, high gradient slopes)
- Badly compacted areas, junctions with civil engineering works such as bridge abutments and inaccessible areas
- Unpredictable or low rainfall areas
- Heavy rainfall areas
- Irrigated areas
- Channels, coastal and seashore protection
- Public and private parks, terraces, dams
- Golf courses
- Lawns temporary reinforcement and protection
- Roads temporary reinforcement

For suppression of weeds please refer to Noweed materials https://www.permathene.co.nz/shop/14-noweed-weed-matting

Outperforms and is more cost-effective than conventional erosion control methods including jute

Composition:

ECB 450 is manufactured from 100% coir fibres which are held together by a photodegradable brown polypropylene netting on both sides

PHYSICAL PROPERTIES		
Property	Value	ECB 450
Physical		
Mass	g/m²	450
Thickness	mm	8 - 10
Open Area	%	65
Service Life	months	24 to 48
Performance		
Max Design Shear Stress	PA	143
Max Slope (Light Velocity Flows)		1H:1V
Max Slope (Moderate Velocity Flows)		1H:1V
Max Slope (Heavy Velocity Flows)		1H:1V
Roll Sizes		
ECB 450 (Brown polypropylene nettin	g both sides)	